



THE ULTRA-SEAL PIG<sup>™</sup> is designed for demanding applications where only minimal product by-pass can be tolerated. The Ultra-Seal<sup>™</sup> delivers as promised with the lowest measurable by-pass in the pigging industry. The Ultra-Seal<sup>™</sup> Pig is available in numerous configurations to meet specific pipeline conditions. Foam density can be varied from 2 pounds per cubic foot through 10 pounds per cubic foot, while the hardness of the elastomeric backbone can be as soft and pliable as 60 Shore A, or as hard and durable as 90 Shore A Durometer.









**BEVELED NOSE** 



## STANDARD

The Ultra-Seal<sup>™</sup> Pig with the Beveled Nose is designed for use in pipelines with slight changes in pipe diameter.

## **EZ-LAUNCH™ NOSE**

The standard Ultra-Seal<sup>™</sup> Pig has flat, polyurethane elastomer discs on each end. This is the optimum design for dewatering, batching of dissimilar products, and for fluid removal in pipelines of all sizes and pipe materials.

The Ultra-Seal<sup>™</sup> Pig with EZ-Launch Nose is designed for use in pipelines with vertical launchers or changes in pipe diameter due to varying wall thicknesses or weld beads common in HDPE piping.

phone: 281.401.8142 toll free: 888.973.0079 fax: 281.401.8147

Tomball, TX 77375

27731 Commercial Park Rd

www.inlineservices.com sales@inlineservices.com