

APACHE LSXDB4L LIMIT SWITCH FOR MODEL 53 & 55 pigPRO™ INDICATORS

PRODUCT SPECIFICATIONS

Availability	Global
Operating Force (O.F.)	17.79 N max. [4 lb max.]
Pretravel (P.T.)	1.78 mm max. [0.070 in max.]
Overtravel (O.T.)	4.83 mm min. [0.190 in min.]
Differential Travel (D.T.)	0.51 mm max. [0.020 in max.]
Product Type	Weather-Sealed, Explosion-Proof Limit Switches
Actuator	Top Roller Plunger
Circuitry	2NC 2NO Double-Pole Double-Throw, Snap-Action, Double-Break
Ampere Rating	10 A (Thermal)
Supply Voltage	600 Vac and 250 Vdc max.
Housing Material	Zinc Die-Cast
Termination Type	0.75 in - 14NPT conduit
Housing Type	LSX Non Plug-in
Series Name	LSX Series
Sealing	NEMA 1, 3, 4, 6, 7 (Class 1, Division 1, Groups B, C, D), 9 (Class 2, Division 1, Groups E, F, G), 13
Approvals	UL listed, CSA Certified
CSA File #	LR57327
UL File #	E61730
Operating Temp. Range	-40 °C to 93 °C [-40 °F to 200 °F]
Comment	Head can be set at 90 degree increments for cam or slide actuation
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Explosion-proof
Operating Position (O.P.)	68.6 mm [2.7 in]

AVAILABLE AT OUR
U.S. DISTRIBUTOR



GEN-LSX-03/17